

# Changes to the third edition following December 2008 update

---

Section Page Amendment

## Introduction

Contents		Appendix G added.
Table 1	2	New robust details E-WM-15 and E-WT-3 added.
Table 2	3	New robust details E-FC-8 added.
Table 3a	4	New robust details E-FC-8, E-WM-15 and E-WT-3 added with acceptable combinations. E-WS-2 combinations revised.
Table 3b	5	New robust details E-WM-15, and E-WT-3 added with relevant notes. Note F added.
Table 3c	5	New robust details E-WM-15, E-WT-3 added with relevant notes.
Table 4	6	New robust details E-WM-15 and E-WT-3 added.
Table 5	6	New robust details E-FC-8 added.
Table 6	7	New robust details E-WM-15, E-WT-3 added with acceptable combinations.

## Separating Wall – Masonry

### E-WM-7

---

Notification that E-WM-7 has now been removed, and that E-WM-10 and E-WM-13 should be used instead.

### E-WM-10

---

DO box	1	Note added to ensure only solid blocks (i.e. not hollow or cellular) are used.
--------	---	--

### E-WM-13

---

DO box	1	Note added to ensure only solid blocks (i.e. not hollow or cellular) are used.
--------	---	--

### E-WM-15

---

All	1-6	New robust detail added – masonry - aircrete blockwork, minimum 75mm cavity with Saint Gobain-Isover RD35 partial fill insulation and gypsum-based board wall finish.
-----	-----	---

## Separating Wall – Timber

### E-WT-3

---

All	1-8	New robust detail added – twin-leaf separating wall using ElecoFrame prefabricated panels.
-----	-----	--

## Separating Floor – Concrete

### E-FC-8

---

All	1-6	New robust detail added – bonded resilient floor cover to floating screed on precast planks.
-----	-----	--

### E-FC-10

---

Detail 1	2	Alternative perimeter detail added.
Detail 3	3	Alternative perimeter detail added.
Detail 6	5	Alternative perimeter detail added.

Section Page Amendment

## Appendix G

1	New appendix added – Determination of the acoustic performance for bonded resilient floor coverings used with RD concrete separating floor E-FC-8.
---	--