E-FT-4

CHECKLIST (to be completed by site manager/supervisor)

Ref. Item Yes No Inspecter 1. Are timber Finnjoists at least 220mm deep? (initials & data data data data data data data da	
Ref. Item Yes No Inspecter 1. Are timber Finnjoists at least 220mm deep? (initials & data) 2. Where used, is rip detail correct? (initials & data) 3. Are SoundBar perimeter edge strips installed correctly? (initials & data) 4. Has the SoundBar floating floor treatment been fitted in accordance with the manufacturer's instructions? (initials & data) 5. Are resilient ceiling bars fitted at right angles to the joists? (initials & data) 6. Has quilt (min 100mm thick) been fitted between the joists? (initials & data) 7. Has ceiling system been fitted in accordance with the manufacturer's instructions? (initials & data) 8. Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? (initials & data)	
 Are timber Finnjoists at least 220mm deep? Where used, is rip detail correct? Are SoundBar perimeter edge strips installed correctly? Has the SoundBar floating floor treatment been fitted in accordance with the manufacturer's instructions? Are resilient ceiling bars fitted at right angles to the joists? Has quilt (min 100mm thick) been fitted between the joists? Has ceiling system been fitted in accordance with the manufacturer's instructions? Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	
 Are timber Finnjoists at least 220mm deep? Where used, is rip detail correct? Are SoundBar perimeter edge strips installed correctly? Has the SoundBar floating floor treatment been fitted in accordance with the manufacturer's instructions? Are resilient ceiling bars fitted at right angles to the joists? Has quilt (min 100mm thick) been fitted between the joists? Has ceiling system been fitted in accordance with the manufacturer's instructions? Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	ato)
 Are SoundBar perimeter edge strips installed correctly? Has the SoundBar floating floor treatment been fitted in accordance with the manufacturer's instructions? Are resilient ceiling bars fitted at right angles to the joists? Has quilt (min 100mm thick) been fitted between the joists? Has ceiling system been fitted in accordance with the manufacturer's instructions? Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	alej
 Has the SoundBar floating floor treatment been fitted in accordance with the manufacturer's instructions? Are resilient ceiling bars fitted at right angles to the joists? Has quilt (min 100mm thick) been fitted between the joists? Has ceiling system been fitted in accordance with the manufacturer's instructions? Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	
 accordance with the manufacturer's instructions? Are resilient ceiling bars fitted at right angles to the joists? Has quilt (min 100mm thick) been fitted between the joists? Has ceiling system been fitted in accordance with the manufacturer's instructions? Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	
 6. Has quilt (min 100mm thick) been fitted between the joists? 7. Has ceiling system been fitted in accordance with the manufacturer's instructions? 8. Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	
 7. Has ceiling system been fitted in accordance with the manufacturer's instructions? 8. Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	
 manufacturer's instructions? Are the ceiling treatments fixed to the resilient bars with correct screws, such that the screws do not touch or penetrate the joists? 	
correct screws, such that the screws do not touch or penetrate the joists?	
9. Is service void minimum 100mm?	
10. Are all joints sealed with tape or caulked with sealant?	
11. Are vertical service pipes wrapped in quilt and boxed in with two layers of gypsum-based board combined nominal mass per unit area of 16 kg/m ² ?	
12. Is separating floor satisfactorily complete?	
Contact details for technical assistance from Finnforest, manufacturer of SoundBar floor system:	
Telephone: 01205 883835 Fax: 01205 362519 E-mail: soundbar@finnforest.com	
Notes (include details of any corrective action)	
Site manager/supervisor signature	

® UK registered trade mark no. 2291665

© Robust Details Limited 2011. All rights reserved. No part of this Handbook (other than the checklists) may be reproduced in any material form or issued or communicated to the public (including photocopying or storing it in any medium by electronic means, and whether or not transiently or incidentally to some other use of this Handbook) without the prior written permission of Robust Details Limited except in accordance with the provisions of the Copyright, Designs and Patents Act 1988.

Warning: the doing of an unauthorised act in relation to a copyright work may result in both a civil claim for damages and criminal prosecution.