

Changes to the third edition following August 2008 update

Section Page Amendment

Introduction

Table 1	2	New robust details E-WM-14 and E-WS-4 added
Table 2	3	New robust details E-FC-9, E-FC-10, E-FT-4 and E-FS-2 added
Table 3a	4	New robust details E-FC-9, E-FC-10, E-WM-14 and E-WS-4 added with acceptable combinations. E-WM-6 combinations revised and note 3 added. Note 1 revised.
Table 3b	5	New robust details E-WM-14, E-WS-4 and E-FT-4 added with acceptable combinations
Table 3c	5	New robust details E-WM-14, E-WS-4 and E-FS-2 added with acceptable combinations. Note 2 added
Table 4	6	New robust details E-WM-14 and E-WS-4 added
Table 5	6	New robust details E-FC-9, E-FC-10, E-FT-4 and E-FS-2 added. Note W3 revised and note W4 added
Table 6	7	New Table added regarding application of proprietary flanking details specified in Appendix A

Separating Wall – Masonry

E-WM-8

Isometric	1	Isometric now illustrates brand identification
Detail 9	6	Integral flue block detail added
All	1-8	All references to RD35 thickness now state 35mm (min)

E-WM-14

All	1-8	New robust detail added – masonry - lightweight aggregate blockwork, 100mm minimum cavity with Isover RD35 partial fill insulation and gypsum-based board wall finish
-----	-----	---

Separating Wall – Steel

E-WS-4

All	1-8	New robust detail added – steel frame separating wall for use with masonry and timber clad external walls
-----	-----	---

Separating Floor – Concrete

E-FC-5

Isometric	1	Ceiling treatment note now makes reference to wall blocks
Detail 1	2	Aircrete blocks added to specification for inner leaf of external wall
Detail 3	3	Ceiling treatment CT5 added for when E-WM-6 is used in combination with E-FC-5
Checklist	6	Point 2 amended to highlight that blocks should be appropriate for planks and ceiling treatment. Point 9 added to check ceiling treatment is appropriate

Section Page Amendment

E-FC-9

All	1-8	New robust detail added – Thermal Economics bonded resilient floor covering to precast planks with direct-applied screed
-----	-----	--

E-FC-10

All	1-8	New robust detail added – Thermal Economics bonded resilient floor covering to in-situ poured slab
-----	-----	--

Separating Floor – Timber

E-FT-4

All	1-8	New robust detail added – Finnforest SoundBar timber floor with Gyvlon screed
-----	-----	---

Separating Floor – Steel

E-FS-2

All	1-6	New robust detail added – UltraBEAM metal joist floor for use with masonry and timber clad external walls
-----	-----	---

Appendix A

Contents	1	Amended to include proprietary flanking constructions
	11	New proprietary flanking construction added – Icopal Monarfloor Bridgestop
	12	New proprietary flanking construction added – Smartroof timber panels for room-in-roof applications

Appendix F

	1-2	Amended to reflect other lightweight floor constructions in addition to the timber floors
--	-----	---