

Changes to the third edition following April 2012 update

Section Page Amendment

Introduction

Table 1	2	New wall references E-WM-22™ and E-WM-23™ added.
Table 3a	4	New wall references E-WM-22™ and E-WM-23™ added with valid combinations.
Table 4	6	New wall references E-WM-22™ and E-WM-23™ added.
Table 6a	7	New wall references E-WM-22™ and E-WM-23™ added.

Separating Wall – Masonry

E-WM-22™

All	1-6	New robust detail™ added – Lightweight aggregate wall with 100mm cavity insulated with Knauf Masonry Party Wall Slab or Superglass Party Wall Roll, and gypsum board finish.
-----	-----	--

E-WM-23™

All	1-6	New robust detail™ added – Aircrete wall with 100mm cavity insulated with Superglass Party Wall Roll, and gypsum board finish.
-----	-----	--

Separating Floor – Timber

E-FT-5™

Diagram 6	5	Revised underfloor heating detail using separate ScreedBoard® 20 and FIBREfon® 8 layers.
Checklist	6	New point 5 added to reflect the revised underfloor heating detail.

E-FT-6™

Diagram 10	7	Revised underfloor heating detail using separate ScreedBoard® 20 and FIBREfon® 8 layers.
Checklist	8	New point 11 added to reflect the revised underfloor heating detail.

Appendix B

Block thickness	1	British Standard reference updated.
-----------------	---	-------------------------------------

